




EURA Drives GmbH

the headquarters of EURA Drives in Europe with more

than 2000m² office, development, training and stock





up-to-date production facilities

and 1200 highly motivated employees

worldwide contribute to the drive development, production, sales and service.





E800 0.4kW - 90 kW

E2000

0.4 kW - 400 kW

Economical IP20, IP21, HVAC frequency inverter for ac induction motor and permanent motor



EM30 0.4 kW - 11 kW

Decentralized drive solution for hard



E600 0.4 kW - 5.5 kW

the compact and economical AC drive



UNIVERSAL

0.4 kW - 400 kW

INVERTER

High-tech motor control concept, based on advanced DSP technology ready for V/Hz, SENSORLESS VECTOR, CLV and permanent magnet

EP66 0.4 kW - 90 kW

the rugged stand alone AC drive with more protections

PUMP INVERTER

0.4 kW - 400 kW

comprehensive special pump software built into each drive as standard, no need of external master controller. PID control concept, multi-set point, cascade control pump staging, solar function, well pump control, level control, Dry run protection and leakage detection function are all in one drive inclusive.



High performace inverter for all your needs

E2100P 0.4 kW - 400 kW

- IP66 remote keypad
- AC, PM motor control
- built in EMC Filter



EM30P 0.4 kW - 11 kW

- built in realtime clock
- full Alu enclosur
- IP67 protection, direct motor mounted



EP66P 0.4 kW - 90 kW

- IP66 stand alone inverter
- Optional built in C1 EMC Filter
- Optional main switch, potentiometer

SOFTSTARTER

HFR 1000 15 kW - 500 kW



HIGHLIGHTS:

For smooth start of any kind of asynchronus motors, reduction of inrush current and mechanical stress.

Startup control mode:

- Current mode: Start ramp at defined current limit
- Voltage mode: Startup at defined voltage ramp
- Boost function

Startup control mode:

- Free stop by inertia
- -Stop controlled by voltage ramp


Controlmode: - Keypad, terminal, MODBUS


Startup control mode:


- Programmable I/O channels
- Integrated LED display, to set parameters and to display drive status

PUMPS CONTROL SYSTEM

- EURA Drives Smart pump software for all EURA AC drives







REGULATED + FIX

Regulated no rotation

Regulated rotation by time

Regulated rotation by sleep **MULTI PUMP**



MULTI PUMP

ALL REGULATED

Fix regulated

Multimaster regulated by time

Multimaster regulated by sleep



PROTECTION FUNCTIONS Dry Run Protection


PROTECTION FUNCTIONS

Filling Protection

AUXILIARY

EURA Drives Smart functions

those functions help the customers to make the services for pumps easier. The life time of pumps will be also extended by using of the functions.



A	Water Flow Detection
В	Pump Cleaning
C	HAND / AUTO Control
D	Antirust & Antifreeze
E	Time Control Mode
F	Autotunning Solar Pump
C	User Macro

APPLICATION

— the EURA AC drives are widely used in many applications



EP66 90kW

Deep well pump drive (up to 150m).

Multiple pump stages for irrigation water supply on different levels. Suitable for decentral power supply (genset), due to low startup current. For outdoor use (with shadowing).

Location: north of italy



Pump inverter EM30P used for pump booster station

Location: Germany



EURA IP20 inverter E2000 used for multi-ventilator

Location: Germany



EP66 used for ventilator 7.5 kW with built in C1 EMC Filter

Location: Germany

EM30 used for Ventilator in high temperature kitchen

Direct mounted on the motor terminal box, short motor cabling, reduced EMV problems, no shielded motor cables required. Compact design, high protection degree, roboust full aluminium construction. Ready for installation in industrial and residential area (C1 filter as internal option available) For critical operating conditions (Heat, dirt/dust, humidity, vibration

Location: Germany





High frequency inverter with high protection degree: IP66 Frequency range up to 1300 Hz Customer specific solutions up to 15 kW

Location: Slovakia



Compact blover/vacuum unit, inverter mounted directly on the motor, high protection degree. Short motor leads, no shielding required, reduced EMC

Location: Germany



EP66 with Add on box

_

Modular enclosure expansion of the EP66 drive: Stainless steel box for different customer specific add-on components, like I/O filters (sinus), chokes, selective motor protection- / bypass switches. Easy to assembly, EP66 protection degree. To order on customers specification, for low quantity as well.

Location: Germany



E2000 400kW

High horsepower inverter in cabinet (up to 800 kW).

Protection degree IP4x.

PFC DC-link choke as standard. Optional mainswitch.

To configure with various customer specific options.

Location: Germany





Mühlenweg 143, 22844 Norderstedt

Telefon: +49 40 589 7950 0 Fax: +49 40 589 7950 29 info@euradrives.eu